

Price list for adhesives TM Henkel from 01.07.2026

Name	Description	Packaging	Price, UAH/ 1 kg
Adhesive for thermovacuum pressing			
AQUENCE FD 144/7	One-component polyurethanedispersion adhesive for3D-gluing PCV, ABS and PET films. The color is white, after drying it is transparent. Viscosity – 2600 MPa, activation temperature from 60° C.	30 kg	503,00
Adhesives for edgebanding			
TECHNOMELT KS 611 white	Filled hot-melt adhesive. Brookfield viscosity - 35 000 mPa * s. Speed from 15 metres per minute, temperature 160-190 ° C.	25 kg	247,00
TECHNOMELT KS 611 transparent			223,00
TECHNOMELT KS 207 transparent.	Filled hot-melt adhesive. Brookfield viscosity - 50 000 mPa * s. Speed from 15-20 metres per minute, temperature 190-210 ° C.	25 kg	213,00
TECHNOMELT KS 217 transparent..	Filled hot-melt adhesive. Brookfield viscosity - 55 000-100 000 mPa * s. Speed from 12 metres per minute, temperature 190-200 ° C.	25 kg	315,00
TECHNOMELT KS 224/2 transparent..	Medium-filled adhesive for edgebanding of curvilinear details. Brookfield viscosity - 17 000-85000 mPa * s. Manual processing. Working temperature 120-140 ° C.	25 kg	307,00
TECHNOMELT KS 351 transparent.	Unfilled adhesive. Brookfield viscosity - 75 000-140 000 mPa * s. Speed from 12 metres per minute, temperature 190-200 ° C.	25 kg	407,00
TECHNOMELT KS 351 white			414,00
TECHNOMELT HKP 21 transparent	Filled hot-melt adhesive in cartridges for machines TM HolzHer. Brookfield viscosity - 87 500 mPa * s. Working temperature 200-220 ° C.	15 kg	486,00
Hot-melt adhesive for wrapping the profiles with paper films			
TECHNOMELT PW 839	Unfilled adhesive. Brookfield viscosity - 5 000-8 500 mPa * s. temperature 170-190 ° C.	25 kg	388,00

Prices are specified in UAH,
incl. VAT